

Flashslide 24 APS-C Sensor 24 Megapixel

Flashslide 36 EXMOR 35 mm Full Frame Sensor 36 MP

Flashslide 42 EXMOR 35 mm Full Frame Sensor 43 MP

- Up to 16 Bit Color Depth
- RAW and JPEG
- IR Mode for Dust and Scratch Removal
- Automatic White Balance
- ARM Processing Unit
- Data Transfer via USB
- HDMI connection

Hardware:

- Combined Touchscreen and Light table
- LED changeable Cold Light Source 5000 K
- 110 – 240 V
- Size 80 x 50 x 30 cm / ca.16 kg

Software :

- Remote Camera Control Ver.3.6
Windows 7 - 8/8.1 – 10 and Mac 10.8-10.11
- Batch Processing
- Common Image Processing Software such as SilverFast, Adobe CS, Capture One, HS ART etc.

APS 17 X 30 mm			
24 X 36 mm			
4,5 x 6 cm			
6 x 6 cm	6 x 7 cm	6 x 8 cm	6 x 9 cm

Gates for Flashslide:

- APS-Film, 35 mm, 4,5 x 6 cm, 6 x 6 cm
6 x 7 cm, 6 x 8 cm, 6 x 9 cm
- All other Gates such as Framed, Single and Film Strip, Pocket 110, Minox, Agfa Rapid, Kodak Instamatic and Disc, Kodak 120, 127, 129, 620, , Zeiss Ikon Taxona, Fotothek Films, etc. on Request
- Roll and Automatic feeds, Slide Magazine on Request

